



**OBJECT POSITION DETECTOR**


**Patent number:** EP0777888  
**Publication date:** 1997-06-11  
**Inventor:** ALLEN TIMOTHY P (US); GILLESPIE DAVID (US);  
MILLER ROBERT J (US); STEINBACH GUNTER (US)  
**Applicant:** SYNAPTICS INC (US)  
**Classification:**  
- **International:** G06K11/16  
- **European:**  
**Application number:** EP19950932385 19950901  
**Priority number(s):** WO1995US11180 19950901; US19940300387  
19940902

**Also published as:**

 WO9607981 (A1)  
 EP0777888 (B1)

Abstract not available for EP0777888  
Abstract of correspondent: **WO9607981**

A proximity sensor system includes a sensor matrix array having a characteristic capacitance on horizontal and vertical conductors connected to sensor pads. The capacitance changes as a function of the proximity of an object or objects to the sensor matrix. The change in capacitance of each node in both the X and Y directions of the matrix due to the approach of an object is converted to a set of voltages in the X and Y directions. These voltages are processed by digital circuitry to develop electrical signals representative of the centroid of the profile of the object, i.e., its position in the X and Y dimensions. Noise reduction and background level setting techniques inherently available in the architecture are employed.



Data supplied from the esp@cenet database - Worldwide